



## C&H 985S (Super Suds)

### Product Description

985S (Super Suds) is a high performance, multi-metal safe, liquid cleaner formulated for use in brush cleaning systems or pressure spray wash systems. 985S provides excellent hard water control and is completely soluble in hot or cold water. 985S provides superior soil cutting ability without the danger of staining, corrosion, or discoloration on vehicle surfaces.

### Performance Features

- Quickly removes road film, greases, oils, and grime from vehicle surfaces
- Contains no phosphates
- Excellent in hard water

### Physical Specifications

Physical State	Liquid
Appearance	Amber
pH	11.5
Rinsability	Excellent

### Equipment Requirements

985S is safe for use with all standard car wash equipment, and low- or high-pressure washers.

### Product Make-Up

C&H 985S is a concentrated vehicle cleaner. Dilute to specified concentration.

### Concentration and Application Method

#### Automatic Car Wash Systems

Add 985S directly to concentrate tank or meter directly into water flow. 985S strength concentration should be 1/2 to 4 oz. per gallon of water. The use of HOT water increases performance. Apply to the surface to be cleaned with high / low pressure spray. Follow with a thorough water rinse.

#### Low- or High-Pressure Washer

For typical vehicle, truck or fleet washing, add 5%-10% by volume of 985S to a low- or high-pressure washer at a temperature between 40°–160° F. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a through water rinse.

#### Brush & Bucket

For typical vehicle, truck or fleet washing, add 5%-10% by volume of 985S to a water-filled bucket at a temperature between 40°–160° F. Apply to surface to be cleaned with sponge or brush. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse.

### Companion Products

Please see Seacole's Industrial Cleaning Catalog.

### Safety and Handling

Please review and understand the C&H 985S SDS before handling.





# Technical Data Sheet

## Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations.

## Ordering Information

C&H 956S is available in 5-gallon pails, 30-gallon drums, 55-gallon drums, and 275-gallon totes.



+1 (763) 582-1140 | +1 (800) 966-2909 | 13505 Industrial Park Blvd. Plymouth, MN 55441 | [seacole.com](https://www.seacole.com)

